

Detailed Specifications



WorkCentre Pro 165 shown with Duplex Automatic Document Feeder, High-Capacity Feeder and Office Finisher Option.



WorkCentre Pro 175 shown with Duplex Automatic Document Feeder, High-Capacity Feeder and Advanced Office Finisher option.



WorkCentre Pro 175 shown with Duplex Automatic Document Feeder, High-Capacity Feeder and Professional Finisher option.

WorkCentre® Pro 165 Advanced Multifunction System	WorkCentre® Pro 175 Advanced Multifunction System
--	--

OUTPUT SPEED—printing and copying

65 images per minute (ipm) letter (8.5 x 11 ⁷ / ₁₆ x 279 mm/A4)	75 images per minute (ipm) letter (8.5 x 11 ⁷ / ₁₆ x 279 mm/A4)
49 ipm legal (8.5 x 14 ¹ / ₂ x 216 x 356 mm)	49 ipm legal (8.5 x 14 ¹ / ₂ x 216 x 356 mm)
42 ipm ledger (11 x 17 ⁷ / ₁₆ x 279 x 432 mm/A3)	42 ipm ledger (11 x 17 ⁷ / ₁₆ x 279 x 432 mm/A3)

FIRST-IMAGE-OUT TIME—letter size, from platen to offsetting catch tray

2.9 seconds	2.9 seconds
-------------	-------------

WorkCentre® Pro 165/175

NETWORK PRINTING—SMart Network Controller

Processor	Intel® Celeron® 433 MHz
Memory	128 MB RAM
System Disk	Minimum 9.1 GB
Printer Languages (auto switching)	PostScript® 3 emulation PCL® 6 (PCL 5e) emulation TIFF (6.0 Old JPEG and New JPEG) TIFF Fax Extended (TIFF-FX) PDF LCDS, SCS, XES and IPDS through third-party transforms

NETWORK PRINTING—resolution, printing via CentreWare® software

PostScript emulation: 600 x 600 and 1200 x 1200 dpi for 128 or 256 levels of gray
PCL emulation: 600 x 600 dpi

WorkCentre® Pro 165/175 Advanced Multifunction Systems

NETWORK PRINTING—printing features*

Edge-to-edge printing
 Secure print
 Delay print (specific time)
 Sample set
 Booklet creation
 Cover selection
 Paper selection by attribute
 Multi-up
 Stapling (single, dual, multiposition)
 Saddle-stitch booklet making (with Professional Finisher)
 Output tray selection
 Watermark
 Fit to new paper size
 Transparency interleave
 Banner sheet enable/disable
 Hole punching
 Image quality
 Save and recall driver settings

PRINT PROTOCOLS AND NETWORKS

Physical	Ethernet 100BaseT/10BaseT, 10Base2, 10Base5 via adapter USB 1.1 port (optional) Wireless ethernet (IEEE 802.11b) via third-party adapters
Operating Systems	Microsoft® Windows® 95, 98, Millennium® (Me), NT® 4.0, 2000, XP®, Windows Server 2003 Citrix Novell® NetWare® 4.x, 5.x, 6 Mac OS® 8.x, 9.x, OS X Solaris® 2.5.1, 2.6 and higher HP-UX® 10.2, 11.x IBM AIX® 4.2 and higher Linux® Intel® <ul style="list-style-type: none"> —Red Hat® —Caldera® —Mandrake™ (LPRNG printing infrastructure) —Corel® (i386) —TurboLinux® (i386) —SuSE® (i386) Linux Power PC® <ul style="list-style-type: none"> —TurboLinux Server 6.0.2
Network Protocols	TCP/IP: Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, NetBIOS, HTTP Netware: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP and NetBEUI

Continued

*Not all features are available in every driver.

WorkCentre® Pro 165/175 Advanced Multifunction Systems

PRINT PROTOCOLS AND NETWORKS *Continued*

Administration Protocols	DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet			
Fonts	PostScript 3: 136 PostScript standard fonts PCL: 80 scalable fonts, line printer and bitmap format line printer fonts Font Management Utility for downloading additional fonts			
Print Drivers	Environment	PCL5e	PCL 6	PostScript
	Windows 95/98/Me	Bidirectional enhanced*	Bidirectional enhanced*	Bidirectional enhanced*
	Windows NT 4.0	Bidirectional with user-selectable interface (standard** and enhanced)	Bidirectional enhanced	Bidirectional with user-selectable interface (standard** and enhanced)
	Windows 2000/XP, Windows Server 2003 (Microsoft certified)	Bidirectional with user-selectable interface (standard and enhanced)	Bidirectional with user-selectable interface (standard and enhanced)	Bidirectional with user-selectable interface (standard and enhanced)
	Macintosh® System 8.x, 9.x, OS X	N/A	N/A	Generic PPD
	Macintosh System 9.x	N/A	N/A	Bidirectional via AppleTalk
Print Submission Tools	Environment	PCL		PostScript
	Solaris 2.4, 2.5.1, 2.6 and higher; IBM AIX 4.2 and higher; LPRNG printing infrastructure; Linux Intel and Linux Power PC	Submission Tool only		Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)
	TIFF/PDF: Supported in Windows 95/98/Me/NT 4.0/2000/XP, Windows Server 2003	Submission Tool for any TIFF or PDF file		

*Enhanced: Xerox custom graphical user interface.

** Standard: Driver based on Microsoft tree-structure user interface (includes Xerox features and functionality).

WorkCentre® Pro 165/175 Advanced Multifunction Systems

DEVICE MANAGEMENT

Management Support	SNMP Version 1 and SNMP Version 2c trap over TCP/IP and IPX MIB access (IETF-MIB II RFC 1213), host resources MIB RFC 2790, Printer MIB RFC v.2
Xerox CentreWare® Internet Services	Allows simple remote installation setting of configuration options and management of the device
Xerox CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system. Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP or 2000 (Professional or Advanced Server) and Internet Explorer 5.01 and higher
Novell NDPS/NEPS (gateway for WorkCentre Pro)	Server gateway application: centralized management tool.
Xerox CentreWare® for Unicenter TNG®	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre Pro under a Unicenter TNG Business Process View.
Xerox CentreWare® for Tivoli® NetView®	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction devices in the general discovery performed by Tivoli NetView.
Xerox CentreWare® MC for Microsoft Management Console (MMC)	CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web Server in NT and Windows 2000 environments.
Xerox CentreWare® for HP® OpenView®	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction devices in the general discovery performed by HP OpenView. Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView.
Xerox Plug and Print 2000	Plug and Print 2000 (PnP2000) is an administrative service program that simplifies enterprise-wide printer installs and relocations for Windows 2000 environments. The product discovers devices, automatically installs devices, enables sharing printers to users and provides install reports—all through a user-friendly interface.
Xerox Barcode Pro PS (optional) Purchase via www.font.net	Enables intelligent PostScript printing on Xerox multifunction printers by storing Xerox software as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.
Xerox Device Types for SAP R/3 Environment	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre Pro printing functionality. (PostScript and PCL): —Simplex or duplex printing —Finishing—single or dual stapling —Tray pull location from any tray —Print security via PIN ID capability at the WorkCentre Pro
Xerox SAP R/3 Intelligent Barcode Utility (optional) Purchase via www.font.net	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox PostScript Device Types for SAP R/3 Environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string, and data compression.

WorkCentre® Pro 165/175 Advanced Multifunction Systems

CENTREWARE® INTERNET SERVICES—integrated device Web page

Device Status	Web server embedded on SMart network controller —Tray status/contents —Consumables status
Print Queue Viewing	Complete job print queue management—hold, release, promote and delete
Job Submission	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Windows XP, 2000/NT 4.0/Me/98/95: Netscape Navigator® 4.x and above, Microsoft Internet Explorer 4.x and above Macintosh 9.x/OS X: Netscape Navigator 6.x Linux: Netscape® Navigator 6.x

NETWORK SCANNING (optional)

Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan-to-network or fax jobs
Input Speed	Scan at 75 ipm (letter/8.5 x 11"/216 x 279 mm/A4 long edge feed [LEF]) at all resolutions
Resolutions	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi
Maximum Scan Area	11.7 x 17"/297 x 432 mm
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX/Windows Server 2003), SMB (Windows NT 4.0/Windows 2000/Windows Server 2003), or Novell NetWare 4.x/5.x/6.x Optional PIN-based guest login
Network Protocol	Novell (NCP via IPX/SPX) FTP via TCP/IP Microsoft SMB via TCP/IP
File Formats	TIFF 6.0 with G3 MH, G4 MMR or JPEG compression (single page or multiple pages) PDF (image only) with G3 MH, G4 MMR or JPEG compression
Document Management Fields	One to six user-programmable metadata fields per scan job Customized fields viewed on WorkCentre Pro user interface Variable data entered using virtual keyboard at WorkCentre Pro
Supported Scan Destinations (Varies by scanning software options purchased)	Scan to network server Scan to remote e-mail destinations via direct SMTP addresses or via various network scanning software options Scan to application (Electronic Document Management System/Repositories) Scan to Microsoft Exchange 2000 Web Folders Scan to Web URL Scan to remote printer Scan to PC Desktop™ (Standard and Deluxe editions) Scan to Windows XP client via WIA (Windows Image Acquisition)

WorkCentre® Pro 165/175 Advanced Multifunction Systems

NETWORK SCANNING SOFTWARE OPTIONS

Network Scanning With E-Mail	<p>Network Scanning – Enables device-specific network scan workflows (destination templates) to be easily created and edited via CentreWare Internet Services. Enables network scanning to the following destinations:</p> <ul style="list-style-type: none"> — Scan to network directory — Scan to e-mail distribution — Scan to Xerox or third-party applications — Scan to Windows XP client (requires WIA driver downloadable from xerox.com)
E-mail (included with Network Scanning Option)	
<i>Capability</i>	Direct document e-mail from device Manual address entry or directory (Exchange/Notes™/LDAP) address searching
<i>Resolutions</i>	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi
<i>Maximum Scan Area</i>	11.7 x 17"/297 x 432 mm/A3
<i>Network Protocol</i>	SMTP, MIME encoded
<i>Authentication</i>	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX/Windows Server 2003), SMB (Windows NT 4.0/Windows 2000/Windows Server 2003), and Novell® NetWare 4.x/5.x/6.x Optional PIN-based guest login
<i>Directory Access</i>	Supports corporate address list via LDAPv3 (Exchange/Notes/e-Directory) Downloaded address list (comma-separated file format)
<i>File Formats</i>	TIFF 6.0 with G3 MH, G4 MMR or JPEG compression (single page or multiple pages) PDF (image only) with G3 MH, G4 MMR or JPEG compression
FreeFlow SMARTsend	<ul style="list-style-type: none"> — A server-based document capture, transformation, conversion and routing software that supports multiple scan-enabled multifunction devices — Enables conversion of scanned documents into a variety of industry standard formats — Workflow creation via web browser Wizards (destinations, document attributes, workflow settings, workflow summary) — Workflow initiation via device scanning User Interface (template selection at device UI) — Destinations: E-Mail, FTP, Microsoft Network Folder, NetWare Folder, Microsoft Exchange 2000 Web Folders, Web URL, Remote Printer — Document Repository Destinations: DocuShare, Domino, Domino.Doc, Microsoft SharePoint
Scan-to-PC Desktop Standard	<ul style="list-style-type: none"> — A desktop and server-based offering that provides document imaging, archiving, editing and organization tools — ScanSoft PaperPort SE 2.0 – image viewing and file management software — ScanSoft OmniPage SE 1.0 (for Distribution Server installation) and ScanSoft OmniPage SE 2.0 (for desktop/client installation) – OCR and file format conversion software — Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre Pro to individual desktops.

Continued

WorkCentre® Pro 165/175 Advanced Multifunction Systems

NETWORK SCANNING SOFTWARE OPTIONS *Continued*

- Scan-to-PC Desktop Deluxe** — A desktop and server based offering that provides document imaging, archiving, editing and organization tools
- ScanSoft PaperPort Pro 9.0 Office – image viewing and file management software
 - ScanSoft OmniPage Pro 11.0 (for Distribution Server installation) and ScanSoft OmniPage Pro 12.0 Office (for desktop/client installation) – OCR and file format conversion software
 - Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre Pro to individual desktops. Also includes an e-mail inbox polling capability.

INTERNET FAX (optional)

Capability	Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP) Reception and automatic printout of documents sent via e-mail from remote Internet Fax machines or e-mail clients
Maximum Scan Area	11.7 x 17"/297 x 432 mm/A3
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX/Windows Server 2003), SMB (Windows NT 4.0/Windows 2000/Windows Server 2003), and Novell Netware 4.x/5.x/6.x Optional PIN-based guest login
Address Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format)
File Formats	TIFF-FX profiles S, F with G3 MH or JPEG compression PDF (image only) with G3 MH, G4 MMR or JPEG compression
Resolutions	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi
Network Protocols	SMTP POP3 (RFC 1939)
Compliance	ITU-T T.37 compliant

NETWORK FAX SERVER INTEGRATION (optional)

	Provides walk-up faxing and hard-copy output of received faxes when integrated with fax-server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration.
Fax Send Features	One- or two-sided scanning (up to ledger/11 x 17"/279 x 432 mm/A3) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, halftone photo, photo, background suppression, seven levels of contrast, seven levels of sharpness)

Continued

WorkCentre® Pro 165/175 Advanced Multifunction Systems

NETWORK FAX SERVER INTEGRATION (optional) *Continued*

Fax Print Features	One- or two-sided printing Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX/Windows Server 2003), SMB (Windows NT 4.0/Windows 2000/Windows Server 2003), and Novell NetWare 4.x/5.x/6.x Optional PIN-based guest login
Supported Network Fax Vendors	Multiple vendors, certified by the Xerox Business Partners Program. For details, visit www.xerox.com
FAX (optional)	
Compatibility	ITU (CCITT) Group 3 quality/resolution of 600 x 600, 300 x 300, 200 x 200, 200 x 100 dpi
Speed/Modem(s)	V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter.
Compression/Speed	MH/MR/MMR/G3/Super G3
Fax Send Features	Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast
Fax Receive Features	One- or two-sided printing, stapled or unstapled Reduction at reception to fit available paper Junk fax prevention
Fax Reports	Activity report Broadcasting/Multipoll Dial directory Transmission confirmation Pending fax Mailbox
Fax Receive Mailboxes	Up to 200 password-protected mailboxes
Auto Dialing	Total of 200 speed dials (single-line option) or 1,000 speed dials (dual-line option) Up to 100 dial groups with up to 200 recipients per group (single-line option) Up to 200 dial groups with up to 400 recipients per group (dual-line option) Auto redial Batch send

WorkCentre® Pro 165/175 Advanced Multifunction Systems

COPYING

Document Scanner	Duplex Automatic Document Feeder with 75-sheet capacity
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 9,999
Resolution	600 x 600 dpi x 8 bit input / 4800 x 1200 dpi output
Concurrency	Concurrent scanning and printing
Digital Imaging	<ul style="list-style-type: none"> AutoIQ automatic digital image quality control Auto rotation 180° or 270° when needed Image shift Edge erase Edge-to-edge copying Auto centering Original type selection (normal, text, halftone, photo) Lighter/darker Background suppression Contrast Sharpness Screening
Copy Pre-collation Memory	512 MB
Reduction/Enlargement	<ul style="list-style-type: none"> Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable percentages
Special Features	<ul style="list-style-type: none"> Auto paper select Auto reduction/enlargement to fit selected paper size Auto registration Auto tray switching Automatic job recovery Booklet creation N-up (up to six columns by six rows for 8.5 x 11"/216 x 279 mm/A4) Transparency dividers (blank or printed) Negative image Mirror image Covers insertion (front only, front and back, back only; blank or printed) Build Job (enables special programming for different pages in one document – can be used for inserts, mixing input from the document glass and document feeder) Page programming of tabs or paper inserts Store and recall job programming Job interrupt Bound document copying (produce multiple sets from stored job segments) Sample set Mixed-size originals Context-sensitive help screens Multiposition stapling with optional Finishers Saddle-stitch booklet making with optional Professional Finisher

Continued

WorkCentre® Pro 165/175 Advanced Multifunction Systems

Copying Continued

Foreign Device Interface (optional)	Interface to third-party access control devices, coin machines, card readers Supports a variety of vending stations available through the Xerox Custom Application Service
USB Port	PC interface for upload/download of internal auditron data and customer device administration/software upgrade
Accessibility Option	Xerox Copier Assistant™ Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.

PAPER HANDLING—Duplex Automatic Document Feeder

Capacity*	75 sheets
Speed	75 ipm—8.5 x 11"/216 x 279 mm long edge feed (LEF)
Paper Sizes Sensed	Statement/5.5 x 8.5"/140 x 216 mm/A5 LEF or short edge feed (SEF) Letter/8.5 x 11"/216 x 279 mm/A4 LEF or SEF Legal/8.5 x 14"/216 x 356 mm SEF Ledger/11 x 17"/279 x 432 mm/A3 SEF
Weights	13 lb to 32 lb bond/50 to 120 gsm

PAPER HANDLING—Front-Loading Paper Trays

Number	Two
Capacity*	550 sheets each
Sizes	User adjustable from 5.5 x 8.5"/140 x 216 mm/A5 to 11 x 17"/279 x 432 mm/A3
Weights	16 lb to 53 lb bond (110 lb index)/60 to 200 gsm
Types	Letterhead Bond Preprinted forms Plain Hole-punched Heavyweight Recycled paper

Continued

*Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

WorkCentre® Pro 165/175 Advanced Multifunction Systems

PAPER HANDLING—Bypass Tray

Capacity*	100 sheets
Sizes	4.13 x 5.83"/105 x 148 mm to 11.7 x 17"/297 x 432 mm
Weights	16 lb to 57 lb bond (80 lb cover)/60 to 216 gsm
Types	Letterhead Bond Preprinted forms Plain Hole-punched Heavyweight Recycled paper Label stock Transparencies

PAPER HANDLING—High-Capacity Feeder

Capacity*	Two trays: 1,600 and 2,000 sheets
Paper Size	Letter/8.5 x 11"/216 x 279 mm/A4 LEF
Weights	16 lb to 53 lb bond (110 lb index)/60 to 200 gsm
Total Capacity*	4,800 sheets (with Bypass Tray, Front-Loading Paper Trays and High-Capacity Feeder)

OUTPUT OPTION—Offsetting Catch Tray Option (WCP 165 only)

Capacity*	300 sheets (Letter/8.5 x 11"/216 x 279 mm/A4)
Sizes	4.25 x 5.5"/A6 to 11 x 17"/A3

OUTPUT OPTION—Office Finisher Option

Top Tray	Capacity:* 250 sheets
Stacking Tray	Capacity:* 2,000 sheets
Sizes	4.25 x 5.5"/A6 to 11 x 17"/A3
Weights	16 lb to 57 lb bond (80 lb cover)/60 to 216 gsm
Stapling	Single (any corner) and dual Auto stapling (50 sheets maximum) Offline stapling (40 sheets maximum) Statement, letter, legal, A5, A4, A3, 11 x 17" sizes supported
Hole Punching	Optional three and two hole punch (North America) Optional two hole and four hole punch (Europe) Optional "Swedish" four hole punch (Europe)

Continued

*Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

WorkCentre® Pro 165/175 Advanced Multifunction Systems

OUTPUT OPTION—Advanced Office Finisher Option

Top Tray	Capacity:* 250 sheets
Stacking Trays	Capacity:* 3,000 sheets (2 x 1,500)
Sizes	4.25 x 5.5"/A6 to 11 x 17"/A3
Weights	16 lb to 57 lb bond (80 lb cover)/60 to 216 gsm
Stapling	Front, rear, dual, SEF and 4-stitch Auto stapling (50 sheets maximum) Offline stapling (50 sheets maximum) Statement, letter, legal, A5, A4, A3, 11 x 17" sizes supported
Hole Punching	Standard three hole punch (North America) Standard two hole punch (Europe) Optional two hole hole punch (North America) Optional four hole punch (Europe) Optional "Swedish" four hole punch (Europe)

OUTPUT OPTION—Professional Finisher Option

Top Tray	Capacity:* 250 sheets
Stacking Tray	Capacity:* 1,500 sheets
Sizes	4.25 x 5.5"/A6 to 11 x 17"/A3
Weights	16 lb to 57 lb bond (80 lb cover)/60 to 216 gsm
Stapling	Front, rear, dual, SEF and 4-stitch Auto stapling (50 sheets maximum) Offline stapling (50 sheets maximum) Statement, letter, legal, A5, A4, A3, 11 x 17" sizes supported
Booklet Maker	Capacity:* Tray stop up, 30 booklets (one to five sheets per booklet); tray stop down, unlimited Sizes: 8.5 x 11"/216 x 279 mm/A4, 8.5 x 14"/216 x 356 mm, 11 x 17"/279 x 432 mm/A3 Weights: 16 to 53 lb bond (100 lb index)/60 to 200 gsm Saddle-stitch capacity:* 2 to 15 sheets (8 to 60 page booklet) V-Fold capacity:* 1 to 5 sheets (unstapled)
Hole Punching	Standard three hole punch (North America) Standard two hole punch (Europe) Optional two hole hole punch (North America) Optional four hole punch (Europe) Optional "Swedish" four hole punch (Europe)

*Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

WorkCentre® Pro 165/175 Advanced Multifunction Systems

ACCOUNTING

Accounting With Third-Party Server Applications (Optional)	Up-to-the-minute data on how the WorkCentre Pro system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax. Multiple accounting vendors, certified by the Xerox Business Partner program. For details, visit www.xerox.com
Internal Auditor	Tracks copy usage Supports up to 2,150 user accounts, 5,925 general accounts and 256 group accounts Auditor report printout available Ability to upload/download account and usage data via direct connection using Microsoft® Windows-based software

WorkCentre® Pro 165

WorkCentre® Pro 175

MONTHLY DUTY CYCLE

Up to 250,000

Up to 300,000

WorkCentre® Pro 165/175 Advanced Multifunction Systems

BASIC CONFIGURATIONS*

Network Multifunction System with Network Controller, High-Capacity Feeder and Duplex Automatic Document Feeder

ACCESSORIES

- One-line fax option
- Two-line fax option
- Office Finisher
- Advanced Office Finisher
- Professional Finisher
- Two-hole legal punch option (N. America)
- Three-hole punch option (N. America)
- Two-hole punch option (Europe)
- Four-hole punch option (Europe)
- “Swedish” Four-hole punch option (Europe)
- Foreign Device Interface
- Offsetting Catch Tray (WCP 165 only)
- Network Accounting Enablement
- Network Scanning With E-Mail
- Network Fax Server Integration
- Internet Fax
- Image Overwrite Security
- FreeFlow SMARTsend Software
- Scan to PC Desktop Client Software
- USB 1.1 Port
- Xerox Copier Assistant

ELECTRICAL REQUIREMENTS

110–140 V Nominal, 60 Hz, 20A or
220–240 V Nominal, 50 Hz, 10A

*Features, configurations and options may vary by location.

	WorkCentre® Pro 165	WorkCentre® Pro 175
POWER CONSUMPTION		
<i>Running</i>	≤ 1,720 watts ¹	≤ 1,720 watts ¹
<i>Standby</i>	≤ 350 watts ²	≤ 350 watts ²
<i>Low Power Mode</i>	≤ 245 watts	≤ 275 watts
<i>Sleep Mode</i>	≤ 95 watts	≤ 95 watts
<i>Warm-up</i>		
<i>Ready to Copy</i>	≤ 72 seconds ³	≤ 72 seconds ³
<i>Ready to Print</i>	≤ 165 seconds	≤ 165 seconds

ENVIRONMENTAL CONSIDERATIONS	
<i>Required Temperature Range</i>	50° to 90° F (10° to 32° C)
<i>Required Relative Humidity</i>	10% to 85%

DIMENSIONS AND WEIGHTS – including shelf	Width	Depth	Height	Weight
<i>Configured with OCT (165 only)</i>	51"/1,297 mm	35"/890 mm	48"/1,230 mm	295 lbs/134 kg
<i>Configured with Office Finisher</i>	61"/1,556 mm	35"/890 mm	48"/1,230 mm	358 lbs/162 kg
<i>Configured with Advanced Office Finisher</i>	67"/1,697 mm	35"/890 mm	48"/1,230 mm	463 lbs/210 kg
<i>Configured with Professional Finisher</i>	69"/1,762 mm	35"/890 mm	48"/1,230 mm	463 lbs/210 kg

SPACE REQUIREMENTS (Moveable)	Width	Depth	Height
<i>Configured with OCT (165 only)</i>	79"/2,007 mm	76"/1,930 mm	78"/1,981 mm
<i>Configured with Office Finisher</i>	89"/2,257 mm	76"/1,930 mm	78"/1,981 mm
<i>Configured with Advanced Office Finisher</i>	95"/2,402 mm	76"/1,930 mm	78"/1,981 mm
<i>Configured with Professional Finisher</i>	97"/2,457 mm	76"/1,930 mm	78"/1,981 mm

¹ ≤ 1,789 watts with Office Finisher
¹ ≤ 1,920 watts with Advanced Office Finisher or Professional Finisher
² ≤ 360 watts with Office Finisher
² ≤ 370 watts with Advanced Office Finisher or Professional Finisher
³ ≤ 82 seconds with Fax enabled

WorkCentre® Pro 165/175 Advanced Multifunction Systems

CERTIFICATIONS

FCC Class A Compliant (U.S.), DOC Class A Compliant (Canada)
 89/336/EEC (Europe)
 UL Listed (UL 1950, Third Edition)
 CB Certified (IEC 60950/EN 60950)
 73/23/EEC (Europe)
 Novell Tested and Approved
 Designed for Microsoft Windows Certified
 99/5/EEC (Europe)

SUPPLIES

<i>Description</i>	<i>Order Number</i>	<i>No. per Box</i>	<i>Expected Yield</i>
Toner Cartridge	6R1146	2	45,000 at 6% area coverage
Staple Cartridge (for 50-sheet stapling)	108R493	3	5,000 per cartridge
Staple Cartridge (for Booklet Maker saddle-stitch stapling) (15 sheet max.)	8R12897	8 (4 x 2)	2,000 per cartridge

Total satisfaction guaranteed.

The exclusive Xerox Total Satisfaction Guarantee, recognized as unique in the industry, covers every Xerox WorkCentre® Pro which has been continuously maintained by Xerox or its authorized representatives under a Xerox express warranty or Xerox Maintenance agreement. You decide when you're satisfied.



© 2004 Xerox Corporation. All rights reserved. XEROX®, CentreWare®, WorkCentre® Pro and Copier Assistant are trademarks of Xerox Corporation. PostScript is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries. Other marks are trademarks or registered trademarks of the companies with which they are associated. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. ENERGY STAR® is a U.S. registered mark. As an ENERGY STAR® Partner, Xerox Corporation has determined that these products meet the ENERGY STAR® guidelines for energy efficiency. Terra Choice Environmental Services, Inc., of Canada has verified that these products conform to all applicable Environmental Choice EcoLogo requirements for minimized impact to the environment. Product information and/or specifications are subject to change without notice. 12/04 610P720220 W75SS-03UA